



Intesis™
BY HMS NETWORKS
INWMPMIT001I000
ME-AC-WMP-1

Wi-Fi interface for Mitsubishi Electric Air Conditioners

1. Introduction

Intesis INWMPMIT001I000 (ME-AC-WMP-1) allows a complete and natural integration of Mitsubishi Electric Air Conditioners into IP based control systems. Compatible with Domestic Air Conditioners commercialized by Mitsubishi Electric.

- Quick and easy installation.
- External power not required.
- Direct connection to the smart hub or home's IP based control system.
- Direct connection to the AC indoor unit.
- Total Control and Supervision.
- Real states of the AC unit's internal variables.
- Allows using simultaneously the Mitsubishi Electric remote controllers¹.

¹ INWMPMIT001I000 is connected to the CN-105 connector, so no other controllers can be connected to this same bus.

2. Dimensions




Figure 2.1 Device dimensions in mm and back view

3. Technical Features

Enclosure	ABS (UL 94 V-0). 2,1 mm thickness
Dimensions	127 x 50 x 17 mm
Weight	80g
Colour	White
Power supply	12V, 60mA typical Doesn't require external power supply (supplied by the AC Unit)
Radio Parameters	RF Frequency range: 2412 to 2484 MHz Output power (average): - 20 dBm (11Mb/Sec.) - 14 dBm (72.2Mb/Sec.)
Mounting	Wall
LED indicators	1 x Device status
Operating Temperature	From 0°C to 40°C
Operating humidity	<93% HR, no condensation
Stock humidity	<93% HR, no condensation
RoHS conformity	Compliant with RoHS directive (2011/65/EU).

Table 3.1 Technical features