imagePROGRAF PRO-2600 / PRO-4600 / PRO-6600







PRO Series






COMPLETE YOUR OBSESSION

Taking a shot is only the first chapter. You pick the best picture from a selection and then edit your files to get the most out of them. However, the story is still incomplete. In a world where we see hundreds of digital images a day, the impact a tangible photo has is remarkable. Especially, if your photo is due to go on display for the world to see. Canon's expertise in capturing and managing images has been the foundation of our photographic range of large format printers. Images have been faithfully reproduced for creative minds all over the world. The new imagePROGRAF PRO Series is designed to showcase your images the way they deserve. Hardware, software and ink technology is optimised to reproduce your work the way you intended it to. Experience full end-to-end control of your image.



KEY FEATURES





POWERFUL WORKFLOW SOLUTIONS

Professional Print and Layout

With Professional Print & Layout to support efficient photo output, Media Configuration Tool to create and register custom media, Device Management Console and Accounting Manager to manage printers, and other software solutions covering photographers and publishers, you can build an efficient workflow. Professional print and layout

Canon's Professional Print & Layout (PPL) software for imagePROGRAF PRO Series printers enables easy professional photo printing with editing and layout tools, as well as colour management capabilities.

Features include:

- Can be used as stand-alone RIP or as export module in Adobe[®]Photoshop[®], Adobe[®] Lightroom, or Canon Digital Photo Professional
- · Create custom templates
- Preview of multiple images at once
- · Save presets
- Crop images
- Auto nesting
- · Black point compensation
- · HDR workflow



FREE LAYOUT PLUS


Lets you nest, tile and create custom layouts before printing your files

ACCOUNTING MANAGER

Centrally manage all your print costs with Accounting Manager. Collect printer job logs, calculate printing costs by job or period, and calculate printing costs for each department or user.







imagePROGRAF **PRO-2600 / PRO-4600 / PRO-6600** SPECIFICATIONS

Print Head PF-10

Number of Nozzles

(1,536 Nozzles x 12 colors)

Droplet Size

Minimum 4pL per color		
Ink Type		
Pigment:	12 colours(Photo Black/Matte Black/Cyan/Magenta/Yellow/Photo Cyan/	
	Photo Magenta/Grey/Photo Grey/Red/Blue/Chroma Optimiser)	
Ink Tank		
Shipped with Printer:	PRO-2600 : 160ml x 12 colours	
	PRO-4600/PRO-6600 : 330ml x 12 colours	
Replacement:	PFI-3100 (160ml)/ PFI-3300 (330ml)/ PFI-3700 (700ml) for PBK/C/M/Y/	
PC/PM/GY/PGY/R/B/	0	
	PEI 2100 (160ml)/ PEI 2200 (220ml)/ PEI 2700 (700ml) for MPK	

Printer RAM 3 GB

500GB (Encrypted)

Hard Disk Media Feed

 Media Feed
 1 Roll, Front-loading, Front output*(*Option for 2nd roll)

 Cut Sheet:
 Front-loading, Front Output (manual)

Media Width

Poster

Others

Media Cutter

0.07 – 0.8 mm

Media Thickness

Media Width			
Roll Paper	PRO-2600	PRO-4600	PRO-6600
ISO	A4, A3, A3+, A2, A2+, A1	A4, A3, A3+, A2, A2+, A1, A0	A4, A3, A3+, A2, A2+, A1, A0
JIS	B4, B3, B2	B4, B3, B2, B1, B0,	B4, B3, B2, B1, B0,
ARCH	12", 18", 24"	12", 18", 24", 30", 36"	12", 18", 24", 30", 36"
Other	6",8", 10", 12", 14", 15", 16", 17", 18", 20", 22", 24" 300mm, 500mm, 600m	6",8", 10", 12", 14", 15", 16", 17", 18", 20", 22", 24", 30", 34", 36", 42", 44" 300mm, 500mm, 600mm, 800mm, 1000mm	6",8", 10", 12", 14", 15", 16", 17", 18", 20", 22", 24", 30", 34", 36", 42", 44", 50", 54", 60", 300mm, 500mm, 600mm, 800mm, 1000mm
Cut Sheet	PRO-2600	PRO-4600	PRO-6600
ISO	A4, A3, A3+, A2, A2+, A1 B4, B3, B2	A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1, B0	A4, A3, A3+, A2, A2+, A1, A0 B4, B3, B2, B1, B0
DIN	C4, C3, C2	C4, C3, C2, C1, C0	C4, C3, C2, C1, C0
JIS	B5, B4, B3, B2	B5, B4, B3, B2, B1, B0	B5, B4, B3, B2, B1, B0
ANSI	9 x 12", 12 x 18", 18 x 24", 24 x 36"	9 x 12", 12 x 18", 18 x 24", 24 x 36"	9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48"
ARCH	9 x 12", 12 x 18", 18 x 24", 24 x 36"	9 x 12", 12 x 18", 18 x 24", 24 x 36"	9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48"
Photo	(20 x 24"), (18 x 22"), (14 x 17"), (12 x 16"), (10 x 12"), (10 x 15"), (8 x 10"), (16 x 20")	(20 x 24"), (18 x 22"), (14 x 17"), (12 x 16"), (10 x 12"), (10 x 15"), (8 x 10"), (16 x 20")	(20 x 24"), (18 x 22"), (14 x 17"), (12 x 16"), (10 x 12"), (10 x 15"), (8 x 10"), (16 x 20")

20 x 30", 30 x 40", 42 x 60", 44 x 62",

300×900mm

13×22'

Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance.

Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types

The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.

20 x 30", 30 x 40",

42 x 60", 44 x 62", 50x70", 54x76", 60x84", 300×900mm

13×22

170mm or less			
Layout, Direct Print Plus	anon Print Service, Devic	e Management Console, F er Driver for Windows®/ Ma ud Link	
Server 2008 R2, (32/64	-bit), Windows Server 20	Vindows 10 (32/64-bit), Wir 12 (64-bit), Windows Serve 10.5-v12x, Windows Serve	er 2012 R2 (64-bit),
Print Language SGRaster, PDF, JPEG			
Interface Hi-Speed USB : Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Ethernet(Built in) : IEEE802.3ab(1000BASE-T)/IEEE802.3u(100BASE-TX)/IEEE802.3(10BASE-T Wireless LAN : IEEE 802.11 b/g /n			
Power Supply AC 100–240V (50 – 60	Hz)		
Power Consumption			
Power Consumption	PRO-2600	PRO-4600	PRO-6600
ISO Power Consumption (using	Approx 85W	Approx 85W	Approx 85W

Consumption (using wired LAN)	Approx 85W	Applox 85W	Approx 85W
Standby(using wired LAN)	Approx 1.7W	Approx 1.7W	Approx 1.7W
Power Off	Approx 0.1W	Approx 0.1W	Approx 0.1W

Operational Environment

Media Core Sizes

Maximum Roll Outer Diameter

2" or 3" Core

Temperature:	15° – 30° C
Relative Humidity:	10-80%
(Non Condensation)	
Printer Dimensions	

Printer Dimensions (W × D × H) and Weight Printer Dimensions PRO-2600 PRO-4600 PRO-6600 Dimensions with stand basket opened (W × D × H) 1110 x 984 x 1168mm 1593 x 984 x 1168mm 1999 x 984 x 1168mm Weight (with Stand) 102kg 124kg 171kg

Package Dimensions (W x D x H) and Weight			
Package Dimensions	PRO-2600	PRO-4600	PRO-6600
Printer with Stand Package Dimen- sions (W x D x H) with pallet	1324 x 912 x 1139mm	1820 x 915 x 1042 mm	2227 x 915 x 1025 mm
Printer with Stand Package Weight	157kg	185kg	222kg
Options			
Options	PRO-2600	PRO-4600	PRO-6600
Roll Unit	RU-23	RU-43	RU-63
Roll Holder	RH2-29	RH2-46	RH2-66

Consumables

PFI-2100/PFI-2300/PFI-2700 for MBK, PFI-3100/PFI-3300/PFI-3700 for other colours

Maintenance Cartridge: MC-30 Cutter Blade: CT-07







Canon Australia Pty Ltd 1800 444 199 canon.com.au/business Canon New Zealand Ltd 0800 222 666 canon.co.nz/business



20 x 30". 300×900mm

13×22'

Automatic horizontal cutting (Rotary Cutter)