

### Secure Access, One Press Away

This exit button features a brushed stainless steel faceplate and a durable, vandal-resistant mechanical button with a built-in LED indicator. Designed to fit standard US single-gang wall boxes, it provides clear "PRESS TO EXIT" labeling and momentary operation. The LED offers visual feedback, making it ideal for offices, secure areas, and access control systems.

### At a Glance

- LED Indicator – Blue light for visual status feedback (6–12V input)
- Stainless Steel Build – Durable 1.7 mm panel with brushed finish
- Momentary Action – Self-resetting mechanical push button
- High Durability – IK10 impact protection, 40,000h LED lifespan
- US Wall Box Compatible – Fits standard single-gang size (115 × 70 mm)



### Specifications

- Dimension: 115 mm (L) × 70 mm (W) × 29.2 mm (H) (±3 mm)
- Material: 1.7mm Stainless steel panel
- Operating Voltage: DC 12 - 24V
- Rated Current: 5A
- Indicator Type: LED
- LED Lifespan: 40,000 hours (typical)
- LED Color: Blue
- LED Working Voltage: 6 - 12V
- Voltage Regulation: Built-in dropper resistor
- Switch Type: Momentary (self-resetting)
- Operating Temperature: -20°C to +50°C
- Storage Temperature: -20°C to +65°C
- Operating Humidity: 10%–90% RH
- Impact Protection Rating: IK10
- Environmental Compliance: RoHS, REACH, Halogen Free