HyPanel Datasheet

New hassle-free smart control panel for your home

The akubela HyPanel, a smart control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- Excellent performance with Android 10 system
- 4" multi-touch screen with energy saving mode
- 2-gang switch, replace conventional switch
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- Kinds of sensors built-in
- EU standard flush mounted box



Basic Information

- Model Number: PS51-R2-EU
- Power Supply: 180 ~ 260VAC, 50Hz
- Built-in Relay Capacity: 16A
- Output: 2 gang, 1200W total;

800W/gang for resistive;

400W/gang for LED/CFL;

Wire Range: $0.5 \sim 2.5 \text{mm}^2$ (24 ~ 12AWG)

- Power Meter: Supported
- Operation System: Android 10
- RAM/ROM: 1GB/8GB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- Ethernet Port: 1×RJ45, 10/100Mbps adaptive

• ZigBee: ZigBee 3.0

• ZigBee Sub-Device Limit: 128

Microphone: Dual microphones, -42dBV

• Speaker: Single speaker, $8\Omega/1.5W$

Appearance

Material: V0 fireproof PC

• Screen: 4" multi-touch screen

• Screen Resolution: 480×480 pixels

• Screen Brightness: 210 cd/m²

Sensors Built In

• Proximity Sensor: 30 ~ 60cm

• Light Sensor: Low-level lux detection

Temperature Sensor: ±1°C, range: -10°C ~
55°C

Humidity Sensor: ±5%, range: 10% ~ 90%RH,
without condensation



Working Environment

• Environment: For indoor use only


 Working Humidity: 10% ~ 90%RH, without condensation


• Working Temperature: -10°C ~ 55°C


• Storage Temperature: -20°C ~ 65°C


• IP Rating: IP20

Product Dimension Diagram (mm)









Installation

• Installation: Wall flush mounting

• Flush Mounted Module: EU/UK standard

• Wiring Way: L- + N- wire required

