

# Poly Edge B30 IP Phone and PoE-enabled

## Call with confidence

Sleek design meets quality audio at an affordable price. Easy-to-use illuminated keys, plug-and-play provisioning, and reliability make it pure value.



\*Product image may differ from actual product

### Crisp audio

Hear every nuance of your call. Poly HD voice and Poly Acoustic Fence technologies give you business-grade audio quality with reduced background noise.

### Easy to use

Simplicity right out of the box. No need to guess if you are on mute, speakerphone, or headset<sup>1</sup>. These keys light up when selected. Instantly add co-workers to your call with 5-way local audio conferencing.

### Totally turnkey

Poly cloud management software makes these phones the smart choice. IT can easily monitor, manage, and maintain devices securely from the cloud with PDMS-SP and Poly Lens software.

Line keys  
4 lines displayed; 16-line key assignments supported with pagination.

Headset compatibility  
More Poly headset options with both RJ9 and 3.5 mm headset ports.<sup>1</sup>

Simple setup  
Simplified network and provisioning with two-port gigabit Ethernet switch 10/100/1000 Base-TX across LAN and PC ports. Zero touch provisioning means these phones are ready right out of the box. Power over ethernet (POE).

Go hands free  
More productive calls with a hands-free speakerphone with proven acoustic echo cancellation and background noise suppression technology.

# Poly Edge B30 IP Phone and PoE-enabled

## Specifications



**Display**

Panel technology: Monochrome LCD  
Display size (diagonal, metric): 71 cm (28")

**Connectivity and communications**

External I/O ports:  
2 RJ-45 (10/100/1000BASE-TX Mbps)

**Battery**

Power features:  
Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 2)<sup>2</sup>

**User interface features**

Languages:  
Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

**Audio**

Audio features:  
Poly HD Voice  
Full-duplex handsfree speakerphone with acoustic echo cancellation and background noise suppression  
Individual volume settings with visual feedback for each audio path  
Voice activity detection  
Comfort noise generation  
DTMF tone generation (RFC 2833 and in-band)  
Low delay audio packet transmission  
Adaptive jitter buffers  
Audio codecs:  
G.711 (A-law and  $\mu$ -law)  
G.722  
G.729AB  
iLBC  
OPUS

**Environmental**

Certifications and compliances: AS/NZS 60950-1; Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-1/14EN 60950-1; CE Mark; CISPR22 Class B; EN 60950-1 & EN 62368-1; EN55024; EN55032 Class B; EN61000-3-2, EN61000-3-3; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; IEC 60950-1 & IEC 62368-1; NZ Telepermit; ROHS compliant; Saudi Arabia CITC; So. Africa ICASA; UAE TRA; UL 60950-1 and UL 62368-1; VCCI Class B; China RoHS 2; ENERGY STAR; Indonesia SDPPt; Mexico NOM ANCE; Russia CU  
Operating humidity range: 5 to 95%  
Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C /  
Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -40 to 70°C /  
Energy star certified: ENERGY STAR® certified

**Certifications**

Special features:  
Unicode UTF-8 character support  
Adjustable desk stand (2 positions)  
Wall mountable

**Applications supported**

Management software:  
Poly Lens  
Poly Zero Touch Provisioning  
Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management  
Web UI to device IP address

**Security**

Security management:  
802.1X Authentication and EAPOL Media encryption via SRTP  
Digest authentication  
HTTPS secure provisioning  
Encrypted configuration files  
Password login  
Transport Layer Security (TLS)  
Support for signed software executables

**Network**

Supported network protocols:  
Administrator password protected  
DHCP VLAN discovery  
LLDP-MED for VLAN discovery  
FTP/TFTP/HTTP/HTTPS server-based central provisioning  
Hardware diagnostics  
Manual or dynamic host configuration protocol (DHCP) network setup  
Network address translation support for static configuration and Keep-Alive  
QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP  
Status and statistics reporting  
Syslog Event Logging  
Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment  
Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation  
Time and date synchronization using SNTP  
SIP signaling  
RTCP and RTP support  
IPv4  
Provisioning and call server redundancy support  
TCP  
DNS-SRV  
UDP  
VoIP features:  
Up to 16 SIP line registrations with pagination key

# Poly Edge B30 IP Phone and PoE-enabled

## Specifications



**Headset and handset compatibility**

**Headset ports:**  
1RJ-9  
13.5 mm headset jack  
1Electronic Hook Switch (EHS) with optional APD-80 adapter

**Headset and handset compatibility:**  
Compatible with commercially available TTY adapter equipment  
Compliant with ADA Section 508 Subpart B 1194.23 (all)  
Hearing aid compatibility to ITU-TP.370 and TIA 504A standards  
Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids

**Telephony and call handling features**

**Telephony and call handling features:**  
16 line keys (configurable, with pagination)  
4 context-sensitive soft keys  
4 line keys with LED  
4 way navigation key cluster with center Select key  
Anonymous call indication  
Background Firmware Updates (TR-69 support)  
Block anonymous call  
Busy Lamp Field (BLF)  
Call forward on busy, on no answer, unconditional  
Call logs (200)  
Call progress tone generation  
Call return  
Call timer and call waiting  
Call transfer, hold, divert (forward), park, pickup  
Caller ID enable/disable  
Daylight savings time support – worldwide  
Dialing from call logs  
Distinctive incoming call treatment/call waiting  
Distinctive ringtones  
Do not disturb function  
Electronic hook switch capable  
Enhanced call park  
Headset select key (illuminated when selected)  
Hold and transfer keys  
Home and back feature keys  
Local five-way audio conferencing  
Message Waiting Indicator (MWI)  
One-touch speed dial, redial  
Page Groups (10)  
Remote missed call notification  
Repeat dialing  
Shared call/bridged line appearance  
Speed Dialing (99 entries, E164 or URI)  
Call hold/resume, diversion (forward), transfer (consultation, blind), pickup  
Calling, called, connected party identification  
Call logs (missed, received, placed)  
4 lines displayed<sup>1</sup>

**Weight and dimensions**

**Product Primary Color:** Black  
**Package dimensions (metric):** 176 x 16.3 x 4.4 cm  
**Package Weight (metric):** 910 g  
**Product number:** 82M84AA

**Country of origin**

**Country of origin:** Made in China

**Warranty**

Poly standard one-year limited warranty

**What is in the box**

Console  
Desk stand/wall mount hardware  
Handset with handset cord  
Network (LAN) cable  
Safety information sheet  
Setup sheet with QR code to documentation and video  
Power supply unit (PSU)

**Key Selling Points Footnotes**

<sup>1</sup> Poly headset sold separately.

**Technical Specifications Footnotes**

<sup>1</sup> Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features. <sup>2</sup> External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).