

Poly CCX 600 Business Media Phone for Microsoft Teams and PoE-enabled

Discontinued

82Z84AA

NI

Specifications

All Specs

Aspect ratio	16:9
Audio	Poly HD Voice; Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset; Poly NoiseBlockAI technology removes most background noise when using the speakerphone; TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex); Individual volume settings with visual feedback for each audio path; Voice activity detection; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ-law); G.722; G.722.1; G.729AB; iLBC; OPUS
Cartons per layer	9
Cartons per pallet	54
Certifications and compliances	Argentina ENACOM; AS/NZS 4268; AS/NZS 62368-1; Australia RCM; Brazil ANATEL; Canada ICES and NRTL; Canada RSS 247 Issue2; China RoHS 2.0; CISPR32 Class B; EEA CE Mark; EN 301 489-1 and EN 301 489-3 and EN 301 489-17; EN 55024; EN 55032 Class B; EN 62368-1; ETSI EN 300 328 and ETSI EN 301 893; Eurasian Customs Union EAC; FCC Part 15 Class B; FCC Part 15.247 and FCC Part 15.407; IC ICES-003 Class B; IEC 60950-1 and IEC 62368-1; India WPC; Indonesia SDPPI; Israel MOC; Japan Article 2.1 Item 19-2 and 19-3; Japan MIC and VCCI; Malaysia SIRIM; Mexico IFETEL and NYCE; New Zealand Telepermit; Saudi Arabia CITC; Singapore IMDA; South Africa ICASA; South Korea KC; Taiwan NCC; UAE TRA; USA FCC and NRTL; UL 62368-1; VCCI Class B
Certified collaboration software	Microsoft Teams
Color	Black
Compatible Operating Systems	Android 12
Country of origin	Made in China, Taiwan or Vietnam
Display features	On-screen virtual keyboard; Adjustable font size selection (regular, medium, large); Screensaver; Voicemail support; Normal and dark mode; Digital picture frame
Display size (diagonal)	17.8 cm (7")
ECCN	5A992
End of Life CO2e (kg)	0.5
Headset and handset compatibility	Bluetooth® headset compatibility; Compatible with commercially available TTY adapter equipment; Compliant with ADA Section 508 Subpart B 1194.23 (all); Hearing aid compatibility to ITU-TP.370 and TIA 504A standards; Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids; USB Type-A headset support; USB Type-C® headset support
Headset ports	1 RJ-9; 1 Electronic Hook Switch (EHS) port for optional adapter
HTS code	8517180020
Layers per pallet	6
Management Software	Poly Lens; Poly Zero Touch Provisioning; Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; Web UI to device IP address

Manufacturer product number	2200-49780-019
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Multiple order quantity	5
Native resolution	1024 x 600
Network protocols, supported	FTP/TFTP/HTTP/HTTPS server-based central provisioning; Hardware diagnostics; Manual or dynamic host configuration protocol (DHCP) network setup; Network address translation support for static configuration and Keep-Alive; QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP; Status and statistics reporting; Syslog Event Logging; Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment; Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation; Time and date synchronization using SNTP; SIP signaling; RTCP and RTP support; IPv4; IPv6; Provisioning and call server redundancy support; DNS-SRV
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	26.3 x 21.7 x 6 cm
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Color LCD
Ports	1 USB 2.0 Type-A (for media and storage applications); 1 USB 2.0 Type-C® (for media and storage applications); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Power	Built-in auto sensing IEEE 802.3at Power over Ethernet (Class 4); 25 W (maximum)
Production CO2e (kg)	50
Products per pallet	270
Products per pallet layer	45
Registration required	No
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)
Special features	Adjustable base height; Unicode UTF-8 character support
Storage temperature range	-40 to 70°C

Telephony and call handling features

Busy Lamp Field (BLF); Call timer and call waiting; Caller ID enable/disable; Distinctive incoming call treatment/call waiting; Do not disturb function; One-touch speed dial, redial; Shared call/bridged line appearance; Automatic off-hook call placement (hot dialing); Call media recording/playback; Automatic/remote answer on headset using electronic hook-switch; Call hold/resume, diversion (forward), transfer (consultation, blind), pickup; Calling, called, connected party identification; Call forward for shared lines; Private hold for shared lines; Call logs (missed, received, placed); Local contact directory; Create local contact from call log; Corporate directory; Call server redundancy (failover); SBC line registration; Conference bridging; Local call forwarding (all, busy, no answer) with destination shown on idle display; Automatic call distribution (ACD); Automatic answer (intercom); Call park/retrieve; Directed call pickup; Group call pickup; Hunt group - sequential calling; Last call return; Auto-answer a page with a muted microphone; PTT and Multicast group; Exchange Calendar Integration; Flexible line keys; Key system emulation; STIR/SHAKEN Caller ID validation; Voice Quality Monitoring (VQMon)

Total CO2e (kg)

80

Touch-enabled

Gesture-based, multi-touch capable touchscreen

Transportation CO2e (kg)

0.4

UNSPSC code

43191508

VoIP features

24 lines (SIP registrations); IETF SIP (RFC 3261 and companion RFCs)

What's in the box

Console; Desk stand; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet

Wireless technologies

Bluetooth® 4.2; Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20); 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

Logistics

ECCN

5A992

HTS code

8517180020

What's in the box

Console; Desk stand; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet

Package dimensions (W x D x H)

26.3 x 21.7 x 6 cm

Pallet dimensions (W x D x H)

101.6 x 121.9 x 149 cm

Country of origin

Made in China, Taiwan or Vietnam

Cartons per layer

9

Cartons per pallet

54

Multiple order quantity

5

Layers per pallet

6

Products per pallet

270

Products per pallet layer

45

Manufacturer product number

2200-49780-019

Material Type for item	FERT
UNSPSC code	43191508
Package weight	300 g
Pallet weight	357 kg

Sustainability

Certifications and compliances	Argentina ENACOM; AS/NZS 4268; AS/NZS 62368-1; Australia RCM; Brazil ANATEL; Canada ICES and NRTL; Canada RSS 247 Issue2; China RoHS 2.0; CISPR32 Class B; EEA CE Mark; EN 301 489-1 and EN 301 489-3 and EN 301 489-17; EN 55024; EN 55032 Class B; EN 62368-1; ETSI EN 300 328 and ETSI EN 301 893; Eurasian Customs Union EAC; FCC Part 15 Class B; FCC Part 15.247 and FCC Part 15.407; IC ICES-003 Class B; IEC 60950-1 and IEC 62368-1; India WPC; Indonesia SDPPI; Israel MOC; Japan Article 2.1 Item 19-2 and 19-3; Japan MIC and VCCI; Malaysia SIRIM; Mexico IFETEL and NYCE; New Zealand Telepermit; Saudi Arabia CITC; Singapore IMDA; South Africa ICASA; South Korea KC; Taiwan NCC; UAE TRA; USA FCC and NRTL; UL 62368-1; VCCI Class B
Country of origin	Made in China, Taiwan or Vietnam
End of Life CO2e (kg)	0.5
Energy Usage CO2e (kg)	29
Production CO2e (kg)	50
Total CO2e (kg)	80
Transportation CO2e (kg)	0.4

Specifications

- [1] Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features.
- [2] External universal AC/DC adapter, 48 VDC, 0.52 A, 25 W (sold separately).
- [3] Ordering an optional power supply unit will be necessary if not Powered over Ethernet with PoE (i. e. using Wi-Fi for network).

Legal disclaimer