

Poly CCX 350 Business Media Phone for Microsoft Teams and PoE-enabled

- Active
- 848Z7AA
- NI

Specifications

All Specs

Audio	Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Individual volume settings with visual feedback for each audio path; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ-law); G.722; G.729A; G.722.1; G.722.1C; G.719; iLBC; OPUS; SILK; Siren™ 14
Cartons per layer	6
Cartons per pallet	42
Certifications and compliances	AS/NZS 62368-1:17; Australia RCM; Brazil ANATEL; CISPR22 Class B; EEA; CE Mark; EN55032 Class B; EN 62368-1; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; Japan MIC/VCCI; NZ Telepermit; Saudi Arabia CITC; So. Africa ICASA; So. Korea KC; UL 62368-1; VCCI Class B; Canada ICES and NRTL; China RoHS 2.0; Indonesia SDPPI; Mexico NYCE; UKCA mark
Certified collaboration software	Microsoft Teams
Color	Black
Compatible Operating Systems	Android 12
Country of origin	Made in China
Display features	Adjustable font size selection (regular, medium, large); Voicemail support; Normal and dark mode; Dedicated Microsoft Teams button
Display size (diagonal)	7.1 cm (2.8")
ECCN	5A992
Energy star certified	ENERGY STAR® certified
Headset and handset compatibility	Compatible with commercially available TTY adapter equipment; Compliant with ADA Section 508 Subpart B 1194.23 (all); Hearing aid compatibility to ITU-TP.370 and TIA 504A standards; Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids; USB Type-A headset support
Headset ports	1 RJ-9
HTS code	8517180020
Layers per pallet	7
Management Software	Poly Lens; Poly Zero Touch Provisioning; Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; Web UI to device IP address
Manufacturer product number	2200-49690
Manufacturer Warranty	Poly standard one-year limited warranty

Material Type for item	FERT
Multiple order quantity	10
Native resolution	640 x 480
Network protocols, supported	FTP/TFTP/HTTP/HTTPS server-based central provisioning; Hardware diagnostics; Manual or dynamic host configuration protocol (DHCP) network setup; Status and statistics reporting; Syslog Event Logging; Time and date synchronization using SNTP; RTCP and RTP support; IPv4; IPv6; Provisioning and call server redundancy support; UDP; IETF SIP (RFC 3261 and companion RFCs)
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	22.2 x 24.3 x 6.9 cm
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Color LCD
Ports	1 USB 2.0 Type-C® (for media and storage applications); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Power	Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0); 13 W (maximum)
Products per pallet	420
Products per pallet layer	60
Registration required	No
Security management	Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); Media encryption via SRT
Special features	Adjustable desk stand (2 positions)
Storage temperature range	-40 to 70°C
Telephony and call handling features	Power over Ethernet (PoE)
UNSPSC code	43191515
UPC number	197497506228
What's in the box	Console; Desk stand; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet

ECCN	5A992
HTS code	8517180020
UPC number	197497506228
What's in the box	Console; Desk stand; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet
Package dimensions (W x D x H)	22.2 x 24.3 x 6.9 cm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Country of origin	Made in China
Cartons per layer	6
Cartons per pallet	42
Multiple order quantity	10
Layers per pallet	7
Products per pallet	420
Products per pallet layer	60
Manufacturer product number	2200-49690
Material Type for item	FERT
UNSPSC code	43191515
Package weight	300 g
Pallet weight	357 kg
Sustainability	
Certifications and compliances	AS/NZS 62368-1:17; Australia RCM; Brazil ANATEL; CISPR22 Class B; EEA; CE Mark; EN55032 Class B; EN 62368-1; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; Japan MIC/VCCI; NZ Telepermit; Saudi Arabia CITC; So. Africa ICASA; So. Korea KC; UL 62368-1; VCCI Class B; Canada ICES and NRTL; China RoHS 2.0; Indonesia SDPPI; Mexico NYCE; UKCA mark
Country of origin	Made in China
Energy star certified	ENERGY STAR® certified

Specifications



[1] Optional wall mount kit can be ordered separately.

[2] External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).

Legal disclaimer