

Poly G7500 Video Conferencing System with Studio E70 and TC10 Controller Kit

Active

92L53AA

NJ

Specifications

All Specs

|                                     |                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio                               | Poly NoiseBlockAI technology; Poly Acoustic Fence technology                                                                                                                                                                                                                                                                    |
| Audio standards                     | 22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M- Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A                                                                                                    |
| Cartons per layer                   | 10                                                                                                                                                                                                                                                                                                                              |
| Cartons per pallet                  | 50                                                                                                                                                                                                                                                                                                                              |
| Certified collaboration software    | Zoom; Microsoft Teams                                                                                                                                                                                                                                                                                                           |
| Color                               | Black                                                                                                                                                                                                                                                                                                                           |
| Content sharing                     | Poly Content App support; Apple AirPlay; Miracast; Digital Whiteboarding; HDMI input                                                                                                                                                                                                                                            |
| Content video resolution (input)    | UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); UXGA (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)                                                                                                                                                       |
| Content video resolution (output)   | UHD (3840 x 2160); WUXGA (1920 x 1200); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA+ (1400 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768)                                                                                                                                                                      |
| Country of origin                   | Made in Laos                                                                                                                                                                                                                                                                                                                    |
| Digital signage                     | Appspace; Raydiant                                                                                                                                                                                                                                                                                                              |
| Dimensions (W x D x H)              | 349.2 x 38.1 x 139.7 mm                                                                                                                                                                                                                                                                                                         |
| Interoperability                    | Microsoft Teams, Zoom certified; Support for native 3rd party applications including BlueJeans, Dialpad, GoToRoom, RingCentral and StarLeaf; All cloud service providers through Poly Video App mode; USB Device mode                                                                                                           |
| Layers per pallet                   | 5                                                                                                                                                                                                                                                                                                                               |
| Management Software                 | Poly Lens                                                                                                                                                                                                                                                                                                                       |
| Manufacturer Warranty               | Poly standard one-year limited warranty                                                                                                                                                                                                                                                                                         |
| Material Type for item              | FERT                                                                                                                                                                                                                                                                                                                            |
| Multiple order quantity             | 1                                                                                                                                                                                                                                                                                                                               |
| Network capabilities                | IPv4; IPv6; 1x 10/100/1G Ethernet; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Dynamic bandwidth allocation; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; 3x 10/100/1G LLN supporting POE+/PSE; RS232 with REST and CLI API support |
| Non-Operating Humidity Range        | 5 to 95%                                                                                                                                                                                                                                                                                                                        |
| Non-operating temperature - Celsius | -40 to 70 °C                                                                                                                                                                                                                                                                                                                    |

|                               |                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating altitude            | 3,048 m                                                                                                                                                                                                                                                                                                                                                                              |
| Operating humidity range      | 15 to 80%                                                                                                                                                                                                                                                                                                                                                                            |
| Operating temperature range   | 0 to 40 °C                                                                                                                                                                                                                                                                                                                                                                           |
| Pallet dimensions (W x D x H) | 120 x 100 x 219.9 cm                                                                                                                                                                                                                                                                                                                                                                 |
| Pallet weight                 | 357 kg                                                                                                                                                                                                                                                                                                                                                                               |
| People video resolution       | 4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps; 4SIF/4CIF, 60 fps from 512 Kbps; 4SIF/4CIF, 30 fps from 128 Kbps; QCIF (176 x 144) from 64 kbps; SIF (352 x 240) from 64 Kbps; CIF (352 x 288) from 64 Kbps; w288p from 128 Kbps; w448 from 384 Kbps; w576p from 512 Kbps |
| Physical security             | Standard Kensington lock slot                                                                                                                                                                                                                                                                                                                                                        |
| Ports                         | 1 USB Type-C® 5Gbps signaling rate; 3 USB Type-A 5Gbps signaling rate; 1 audio-in; 1 audio-out; 1 RS-232; 1 HDMI-in 1.4 (video and audio); 2 HDMI-out 1.4 (video); 1 HDCI; 1 HDMI-out 1.4 (audio)                                                                                                                                                                                    |
| Power                         | 65 BTU h                                                                                                                                                                                                                                                                                                                                                                             |
| Power supply type             | External                                                                                                                                                                                                                                                                                                                                                                             |
| Products per pallet           | 50                                                                                                                                                                                                                                                                                                                                                                                   |
| Products per pallet layer     | 10                                                                                                                                                                                                                                                                                                                                                                                   |
| Registration required         | No                                                                                                                                                                                                                                                                                                                                                                                   |
| Special features              | Auto sensing power supply                                                                                                                                                                                                                                                                                                                                                            |
| UNSPSC code                   | 45111902                                                                                                                                                                                                                                                                                                                                                                             |
| UPC number                    | 197498808079                                                                                                                                                                                                                                                                                                                                                                         |
| Video frame rate              | 5–60 fps (up to 4K resolution at 15 fps in call)                                                                                                                                                                                                                                                                                                                                     |
| Video standards               | H.264 AVC; H.264 High Profile; H.265                                                                                                                                                                                                                                                                                                                                                 |
| Weight                        | 952.5 g                                                                                                                                                                                                                                                                                                                                                                              |
| What's in the box             | Poly G7500; Poly Studio E70; Cable bundle; Poly IP Microphone; AC power adapter; Poly TC10 touch controller                                                                                                                                                                                                                                                                          |

Logistics

|                               |                                                                                                             |
|-------------------------------|-------------------------------------------------------------------------------------------------------------|
| UPC number                    | 197498808079                                                                                                |
| What's in the box             | Poly G7500; Poly Studio E70; Cable bundle; Poly IP Microphone; AC power adapter; Poly TC10 touch controller |
| Pallet dimensions (W x D x H) | 120 x 100 x 219.9 cm                                                                                        |

|                           |                         |
|---------------------------|-------------------------|
| Dimensions (W x D x H)    | 349.2 x 38.1 x 139.7 mm |
| Country of origin         | Made in Laos            |
| Cartons per layer         | 10                      |
| Cartons per pallet        | 50                      |
| Multiple order quantity   | 1                       |
| Layers per pallet         | 5                       |
| Products per pallet       | 50                      |
| Products per pallet layer | 10                      |
| Material Type for item    | FERT                    |
| UNSPSC code               | 45111902                |
| Pallet weight             | 357 kg                  |
| Weight                    | 952.5 g                 |

Sustainability

|                   |              |
|-------------------|--------------|
| Country of origin | Made in Laos |
|-------------------|--------------|

Specifications

[1] Compatibility with native applications and meeting services is limited by each 3rd party service's own terms and certification conditions; consult each service provider's terms as needed.

[2] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Legal disclaimer