

Poly Studio G62 Video Conferencing System With Mounting Plate Kit No Radio TAA

Active

99T21AA

NJ

Specifications

All Specs

Audio	Keyboard noise reduction; MMode; NoiseBlockAI; Sound Reflection Reduction; Instant adaptation echo cancellation; Acoustic Fence; Audio error concealment; Siren Lost Packet Recovery technology; Poly Stereo Audio; Active Lip Synchronization; Automatic gain control (AGC)
Audio standards	22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M- Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A
Cartons per layer	18
Cartons per pallet	126
Certifications and compliances	CB; FCC; IC; RCM; VCCI; UL/CSA; CE; WEEE; UKCA; MIC
Certified collaboration software	Microsoft Teams; Zoom; Poly Video
Color	Black
Compatible Operating Systems	Android
Content sharing	Apple AirPlay; Miracast; Digital Whiteboarding; HDMI input; USB Type-C®
Content video resolution (input)	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768); SXGA+ (1400 x 1050)
Content video resolution (output)	UHD (3840 x 2160); HD (1920 x 1080); HD (1280 x 720)
Country of origin	Made in Laos
Digital signage	Appspace; Raydiant; Zoom
Dimensions (W x D x H)	247.7 x 152.4 x 34.9 mm
Interoperability	Microsoft Teams, Zoom certified; Support for native 3rd party applications including Dialpad, GoToRoom, RingCentral and Tencent
Layers per pallet	7
Management Software	Poly Lens
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Microphone type	Up to three IP microphone arrays
Multiple order quantity	1

Network capabilities	IPv4; IPv6; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; 100/1G/2.5G; IP REST & CLI API support; Simple Certificate Enrollment Protocol (SCEP)
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-40 to 70 °C
Operating altitude	3,048 m
Operating humidity range	15 to 80%
Operating temperature range	32 to 104 °F
Operating voltage	50 – 57 V, 30 W (class 4), 45 W (class 5), 60 W (class 6)
Package dimensions (W x D x H)	304.8 x 187.3 x 84.1 mm
Package weight	1390 g
Pallet dimensions (W x D x H)	120 x 100 x 204 cm
Pallet weight	357 kg
People video resolution	4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps; 4K, 30 fps from 3200 Kbps
Ports	2 USB Type-A 5Gbps signaling rate; 1 HDMI-in 2.0; 1 line in; 1 line out; 2 HDMI-out 2.0 (video); 1 PoE+ 802.3at-class 4 LAN RJ-45; 1 LLN RJ-45; 1 USB Type-C® 5Gbps signaling rate (with DisplayPort™ Alt Mode for video input, 2 lanes 4K @ 30 Hz)
Power	Power over Ethernet (PoE+), compatible with IEEE 802.3at/bt class 4, 5, 6 switch, or PoE injector
Power supply type	External
Products per pallet	126
Products per pallet layer	18
Registration required	No
RMN number	PBJ-STG-62R; PBJ-STG-62N
Security management	802.1x support
Smart camera technology	People framing; Group framing; Presenter tracking; DirectorAI perimeter; Speaker framing
Sustainability specifications	80% post-consumer recycled plastic; Packaging is recyclable; At least 20% recycled metal
UNSPSC code	45111902
UPC number	197961147414
Video frame rate	30 fps (up to 4K resolution)

Video standards

H.264 AVC; H.264 High Profile; H.265; H.264 SVC; H.263; RTV; H.263 video error concealment; H.264 video error concealment; H.239 Polycom People+Content

Weight

798 g

What's in the box

Ethernet cable; Warranty card; HDMI cable; Poly Studio G62

Logistics

UPC number

197961147414

What's in the box

Ethernet cable; Warranty card; HDMI cable; Poly Studio G62

Package dimensions (W x D x H)

304.8 x 187.3 x 84.1 mm

Pallet dimensions (W x D x H)

120 x 100 x 204 cm

Dimensions (W x D x H)

247.7 x 152.4 x 34.9 mm

Country of origin

Made in Laos

Cartons per layer

18

Cartons per pallet

126

Multiple order quantity

1

Layers per pallet

7

Products per pallet

126

Products per pallet layer

18

Material Type for item

FERT

RMN number

PBJ-STG-62R; PBJ-STG-62N

UNSPSC code

45111902

Package weight

1390 g

Pallet weight

357 kg

Weight

798 g

Sustainability

Certifications and compliances

CB; FCC; IC; RCM; VCCI; UL/CSA; CE; WEEE; UKCA; MIC

Country of origin	Made in Laos
Sustainability specifications	80% post-consumer recycled plastic; Packaging is recyclable; At least 20% recycled metal
Sustainability specifications footnote number	[5,6]

Specifications

- [1] Sold separately.
- [2] PoE+ switch must be configured to 30 W or more.
- [3] Not available on no radio versions.
- [4] Poly peripherals may be needed to enable these features.
- [5] Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard.
- [6] Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
- [7] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.
- [8] Compatibility with native applications and meeting services is limited by each 3rd party service's own terms and certification conditions; consult each service provider's terms as needed.

Legal disclaimer