

Poly Studio V52 USB Video Bar No Power Cord TAA

Active

A09D7AA

NJ

Specifications

All Specs

Audio	Full duplex audio; Acoustic echo cancellation; Poly NoiseBlockAI technology; Poly Acoustic Fence technology; Automatic gain control (AGC)
Audio standards	Up to 48 kHz/16 bit/Stereo; UAC 2.0
Camera range (metric)	Up to 6.1 m
Camera resolution	2160p, 4K UHD (3840 x 2160)
Camera type	Single-lens
Cartons per layer	9
Cartons per pallet	90
Certified collaboration software	Google Meet; Microsoft Teams; Zoom
Color	White
Content video resolution (input)	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); UXGA (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)
Country of origin	Made in Laos
Diagonal field of view (dFoV)	110°
Dimensions (W x D x H)	769.5 x 115.2 x 103 mm
Heat dissipation cooling	65 BTU/h
Horizontal field of view (hFoV)	95°
Interoperability	Google Meet, Microsoft Teams, Zoom certified; USB Device mode
Layers per pallet	10
Lens cover capabilities	Attachable
Management Software	Poly Lens Cloud
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT

Microphone pickup range (metric)	Up to 6.09 m
Microphone type	Two MEMS microphones; Two second-order microphones
Multiple order quantity	1
Network capabilities	IPv4; IPv6; 1x 10/100/1G Ethernet; Web proxy support: basic, digest, and NTLM
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-40 to 70 °C
Operating altitude	4,877 m
Operating humidity range	15 to 80%
Operating temperature range	32 to 104 °F
Package dimensions (W x D x H)	850 x 205 x 145 mm
Package weight	3000 g
Pallet dimensions (W x D x H)	120 x 100 x 12.8 cm
Pallet weight	513.3 kg
Physical security	Standard Kensington lock slot
Ports	1 USB Type-C® 5Gbps signaling rate; 1 RJ-11; 2 HDMI-out 2.0 (for provisioning support only); 1 RJ-45 Ethernet port; 1 HDMI-in 1.4 (not supported); 2 USB Type-A 5Gbps signaling rate (disabled by default, can be enabled in Poly Lens app)
Power	37 VA, 120 V 60 Hz; 37 VA, 230 V 50/60 Hz
Power supply type	External
Products per pallet	90
Products per pallet layer	9
Registration required	No
Security management	AES 128 bits encryption; AES 256 bits encryption; Authenticated access to admin menus, web interface, and APIs; BFCP; Local account password policy configuration
Sensitivity (speaker)	79 dB
Smart camera technology	Poly DirectorAI with speaker framing; People framing; Group framing; DirectorAI perimeter
Speaker output power	2 x 20 W (40 W maximum)
Speaker type	Dual speakers

Total camera resolution (megapixels)	20 MP
UNSPSC code	45121520
UPC number	198122618408
Video frame rate	30 fps
Video standards	UVC 1.1, up to 4K NV12 30 fps, 4K MJPEG 30 fps
Weight	2540 g
What is in the box footnote	[2]
What's in the box	Monitor clamp; Privacy cover; Quick start guide; Warranty card; Product notice; AC power adapter; HDMI cable; Poly Studio V52; USB Type-C® to USB Type-C® cable; Safety documents; Compliance documents
Wireless technologies	Wi-Fi 802.11a/b/g/n/ac/ax (MIMO) Multi-channel Concurrency; Bluetooth® 5.0 (audio sink not supported)
Zoom capability	5x digital

Logistics

UPC number	198122618408
What's in the box	Monitor clamp; Privacy cover; Quick start guide; Warranty card; Product notice; AC power adapter; HDMI cable; Poly Studio V52; USB Type-C® to USB Type-C® cable; Safety documents; Compliance documents
What is in the box footnote	[2]
Package dimensions (W x D x H)	850 x 205 x 145 mm
Pallet dimensions (W x D x H)	120 x 100 x 12.8 cm
Dimensions (W x D x H)	769.5 x 115.2 x 103 mm
Country of origin	Made in Laos
Cartons per layer	9
Cartons per pallet	90
Multiple order quantity	1
Layers per pallet	10
Products per pallet	90
Products per pallet layer	9
Material Type for item	FERT

UNSPSC code	45121520
Package weight	3000 g
Pallet weight	513.3 kg
Weight	2540 g

Specifications

[1] USB Type-A ports will only support mouse and keyboard peripherals.

[2] Included power cable may vary by country.

[3] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

[4] Compatibility with native applications and meeting services is limited by each 3rd party service's own terms and certification conditions; consult each service provider's terms as needed.

Legal disclaimer