

Poly Studio Base Kit G9 Plus for Microsoft Teams HP Mini IP PC w/TC10

- Active
- A3LU8AA
- NJ

Specifications

All Specs

Aspect ratio	16:10
Brightness	300 nits
Cartons per layer	8
Cartons per pallet	56
Certified collaboration software	Microsoft Teams Rooms
Chipset	Intel® Q670 (vPro®)
Contrast ratio	1000:1
Country of origin	Mexico(ABT, UUF, ABB, UUZ, ABG, AB1, ABU, AB0, ABA, ABM, ABJ, AB2, AR6)
Dimensions (W x D x H)	177 x 175 x 34 mm (HP Mini IP Conference PC); 260 x 184 x 64 mm (Poly TC10 Touch Controller)
Display size (diagonal)	25.7 cm (10.1")
Expansion slots	1 M.2 2230; 2 M.2 2280
Expansion slots note	1 M.2 2230 slot for WLAN and 2 M.2 2280 slots for storage
Graphics	Integrated
Graphics (integrated)	Intel® UHD Graphics 770
Horizontal viewing angle	75°
I/O Port location	Rear
Internal Storage	256 GB PCIe® NVMe™ M.2 SSD
Layers per pallet	7
Manageability Features 1	HP Image Assistant (download)
Manageability Features 2	HP Manageability Integration Kit (download)
Manageability Features footnote number 2	[4]

Management features	HP Console Control; Poly Lens
Management Software	Poly Lens; Device Management Service
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	UNBW
Memory	16 GB DDR5-4800 MHz RAM (2 x 8 GB)
Memory and storage	16 GB memory; 256 GB SSD storage
Memory Slots	2 SODIMM
Multiple order quantity	1
Native resolution	WXGA (1280 x 800)
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-20 to 60 °C
Operating altitude	3,048 m
Operating humidity range	10 to 90% RH
Operating system	Windows 11 IoT Enterprise
Operating temperature range	10 to 35°C
Package dimensions (W x D x H)	510 x 275 x 280 mm
Package weight	6800 g
Pallet dimensions (W x D x H)	120 x 100 x 213 cm
Pallet weight	381 kg
Panel technology	IPS
Physical security	Standard Kensington lock slot
Ports	1 USB Type-C® 10Gbps signaling rate (DisplayPort™); 1 USB Type-C® 10Gbps signaling rate; 3 USB Type-A 10Gbps signaling rate; 1 HDMI 2.0b; 1 HDMI 2.1b; 1 RJ-45; 1 standard lock slot; 1 power connector; 2 DisplayPort™ 1.4a; 1 PoE 2.5Gbps signaling rate
Power	150 W external power adapter, up to 89% efficiency
Processor	Intel® Core™ i7-13700T (up to 4.9 GHz with Intel® Turbo Boost Technology, 30 MB L3 cache, 16 cores, 24 threads)
Processor family	13th Generation Intel® Core™ i7 processor

Products per pallet	56
Products per pallet layer	8
Registration required	No
Security management	HP Sure Start Gen7
Software included	Microsoft Teams Rooms
Standard memory note	Transfer rates up to 4800 MT/s.
UNSPSC code	45111902
UPC number	198415145970
Vertical viewing angle	75°
Weight	1.42 kg (HP Mini IP Conference PC); 1.27 kg (Poly TC10 Touch Controller)
What is in the box footnote	[5,6]
What's in the box	Ethernet cable; Setup sheet; Warranty card; AC power adapter; Power cable; Poly TC10 touch controller; HP Mini IP Conference PC with Microsoft Team Rooms; HP DisplayPort to HDMI True 4K Adapter; HP Deskop Mini Port Cover v3; HP Desktop Mini v4+ VESA Sleeve with Power Supply Holder
Wireless	Intel® Wi-Fi 6E AX211 (2x2) and Bluetooth® 5.3 wireless card (supporting gigabit data rate)

Logistics

UPC number	198415145970
What's in the box	Ethernet cable; Setup sheet; Warranty card; AC power adapter; Power cable; Poly TC10 touch controller; HP Mini IP Conference PC with Microsoft Team Rooms; HP DisplayPort to HDMI True 4K Adapter; HP Deskop Mini Port Cover v3; HP Desktop Mini v4+ VESA Sleeve with Power Supply Holder
What is in the box footnote	[5,6]
Package dimensions (W x D x H)	510 x 275 x 280 mm
Pallet dimensions (W x D x H)	120 x 100 x 213 cm
Dimensions (W x D x H)	177 x 175 x 34 mm (HP Mini IP Conference PC); 260 x 184 x 64 mm (Poly TC10 Touch Controller)
Country of origin	Mexico(ABT, UUF, ABB, UUZ, ABG, AB1, ABU, AB0, ABA, ABM, ABJ, AB2, AR6)
Cartons per layer	8
Cartons per pallet	56
Multiple order quantity	1

Layers per pallet	7
Products per pallet	56
Products per pallet layer	8
Material Type for item	UNBW
UNSPSC code	45111902
Package weight	6800 g
Pallet weight	381 kg
Weight	1.42 kg (HP Mini IP Conference PC); 1.27 kg (Poly TC10 Touch Controller)

Sustainability

Country of origin	Mexico(ABT, UUF, ABB, UUZ, ABG, AB1, ABU, AB0, ABA, ABM, ABJ, AB2, AR6)
-------------------	---

Specifications

[1] Intel vPro® on this product requires a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>.

[2] Multi-core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

[3] Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost/> for more information.

[4] HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

[5] Included power cable may vary by country.

[6] Poly TC10 touch controller comes in the box with the following accessories: Wall mount kit; Table stand; Mounting hardware; RJ-45 cable; Quick start QR code; Warranty card; Poly Lens coaster.

[7] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Legal disclaimer