

Poly Studio V72 USB Video Bar

- Active
- AV1E3AA
- NJ

Specifications

All Specs

Audio	Poly NoiseBlockAI technology; Poly Acoustic Fence technology; Automatic gain control (AGC)
Camera range (metric)	Up to 7.62 m
Camera resolution	2160p, 4K UHD (3840 x 2160)
Camera type	Dual-lens
Cartons per layer	7
Cartons per pallet	63
Certified collaboration software	Microsoft Teams; Zoom
Color	White
Country of origin	Laos(ABU, AR6, UUF, ABT, ABA, ACJ, ABM, AC3, ABG, AB2, ABB)
Diagonal field of view (dFoV)	140° (wide); 78° (narrow)
Dimensions (W x D x H)	840.18 x 135.4 x 117.93 mm
Heat dissipation cooling	65 BTU/h
Horizontal field of view (hFoV)	120° (wide); 70° (narrow)
Interoperability	Microsoft Teams, Zoom certified; USB Device mode
Layers per pallet	9
Lens cover capabilities	Integrated
Management Software	Poly Lens Cloud; Poly Lens Room
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Microphone pickup range (metric)	Up to 7.62 m
Microphone type	Two MEMS microphones; Two second-order microphones

Multiple order quantity	1
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-40 to 70 °C
Operating altitude	4,877 m
Operating humidity range	15 to 80%
Operating temperature range	0 to 40°C
Operating voltage	37 VA @ 120 V @ 60 Hz; 37 VA @ 230 V @ 50/60 Hz
Package dimensions (W x D x H)	920 x 163 x 228 mm
Package weight	6261 g
Pallet dimensions (W x D x H)	120 x 100 x 221 cm
Pallet weight	420 kg
Physical security	Standard Kensington lock slot
Ports	1 USB Type-C® 5Gbps signaling rate; 1 RJ-11; 2 HDMI-out 2.0 (for provisioning support only); 1 LLN RJ-45; 1 HDMI-in 1.4 (not supported); 1 line in (not supported); 1 line out (not supported); 1 LAN RJ-45; 2 USB Type-A 5Gbps signaling rate (disabled by default, can be enabled in Poly Lens app)
Power supply type	External
Products per pallet	63
Products per pallet layer	7
Registration required	No
RMN number	PATX-STX-72R; PATX-STX-72N
Security management	Local account password policy configuration; Security profiles; Secure defaults; Remote logging with support for TLS
Sensitivity (microphone)	-26 dB
Sensitivity (speaker)	83 dB (mid speakers); 89 dB (tweeter speakers)
Smart camera technology	Poly DirectorAI with speaker framing, people framing, group framing
Speaker output power	2 x 20 W (RMS for mid speakers); 2 x 30 W (maximum for mid speakers); 2 x 15 W (RMS for tweeter speakers); 2 x 20 W (maximum for tweeter speakers)
Sustainability specifications	Contains recycled plastics; Paper-based packaging derived from at least 60% recycled materials
Total camera resolution (megapixels)	2 x 20 MP

UNSPSC code	45121520
UPC number	(ABB) 198828966025; (ABG) 198828966032; (ABM) 199251229077; (ABU) 198828966049; (AC3) 198701635314; (AR6) 199251229084; (UUF) 199251229091
Video frame rate	30 fps
Weight	3307 g
What is in the box footnote	[6]
What's in the box	Wall mount kit; Quick start guide; AC power adapter; HDMI cable; Power cable; USB Type-C® to USB Type-C® cable; Poly Studio V72; Ethernet cable (2 m)
Wireless technologies	Wi-Fi 802.11a/b/g/n/ac/ax (MIMO) Multi-channel Concurrency
Zoom capability	7.3x digital

Logistics

UPC number	(ABB) 198828966025; (ABG) 198828966032; (ABM) 199251229077; (ABU) 198828966049; (AC3) 198701635314; (AR6) 199251229084; (UUF) 199251229091
What's in the box	Wall mount kit; Quick start guide; AC power adapter; HDMI cable; Power cable; USB Type-C® to USB Type-C® cable; Poly Studio V72; Ethernet cable (2 m)
What is in the box footnote	[6]
Package dimensions (W x D x H)	920 x 163 x 228 mm
Pallet dimensions (W x D x H)	120 x 100 x 221 cm
Dimensions (W x D x H)	840.18 x 135.4 x 117.93 mm
Country of origin	Laos(ABU, AR6, UUF, ABT, ABA, ACJ, ABM, AC3, ABG, AB2, ABB)
Cartons per layer	7
Cartons per pallet	63
Multiple order quantity	1
Layers per pallet	9
Products per pallet	63
Products per pallet layer	7
Material Type for item	FERT
RMN number	PATX-STX-72R; PATX-STX-72N
UNSPSC code	45121520

Package weight	6261 g
Pallet weight	420 kg
Weight	3307 g

Sustainability

Country of origin	Laos(ABU, AR6, UUF, ABT, ABA, ACJ, ABM, AC3, ABG, AB2, ABB)
Sustainability specifications	Contains recycled plastics; Paper-based packaging derived from at least 60% recycled materials
Sustainability specifications footnote number	[2,3]

Specifications

- [1] USB Type-A ports will only support mouse and keyboard peripherals.
- [2] Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 16801-2018 standard.
- [3] Percent of paper-based packaging made from sustainably sourced, certified, and recycled fibers.
- [4] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.
- [5] TAA, JITC and no radio versions available.
- [6] AC3 localization does not include the power cable.

Legal disclaimer