

HP Poly Studio A2 Audio Bridge w/ CAT6A and Mic Extension Cable and Mounting Plate

- Active
- B22X2AA
- NJ

Specifications

All Specs

Audio standards	A2B Audio Bus
Cable length	6 m
Cartons per layer	10
Cartons per pallet	40 (air); 50 (ocean)
Color	Black
Compatibility	Compatible with Poly Studio G62, Poly Studio X72 and Poly Studio V72, Poly Studio X52 and Poly Studio V52, Poly Studio X32[1].
Country of origin	Taiwan(ABT, AC3); Thailand(ABT, AC3)
Dimensions (W x D x H)	147 x 103 x 24 mm
End of Life CO2e (kg)	0.5
Layers per pallet	4 (air); 5 (ocean)
Management Software	Poly Lens
Manufacturer Warranty	HP standard one-year limited warranty
Material Type for item	FERT
Multiple order quantity	5
Network capabilities	1x 10/100/1G Ethernet
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-40 to 70 °C
Operating altitude	3,048 m
Operating humidity range	15 to 80%
Operating temperature range	32 to 104 °F
Operating voltage	56 V

Package dimensions (W x D x H)	327 x 213 x 89 mm
Package weight	1800 g
Pallet dimensions (W x D x H)	120 x 100 x 154.5 cm (ocean); 120 x 100 x 190 cm (air)
Pallet weight	382.2 kg
Physical security	Standard Kensington lock slot
Ports	1 RJ-45 Ethernet port; 4 A2B bus ports
Power	Power over Ethernet (PoE+/++), compatible with IEEE 802.3at/bt Class 4, 5, 6, 8; 100 - 240 V, 2 A, 50/60 Hz
Power supply type	External
Production CO2e (kg)	71
Products per pallet	200 (air); 250 (ocean)
Products per pallet layer	50
Registration required	No
Special features	Poly StudioNet
Sustainability specifications	Contains at least 45% recycled plastic content; Paper-based packaging
Total CO2e (kg)	100
Transportation CO2e (kg)	3
UNSPSC code	45111704
UPC number	(AB1) 199642005488; (AC3) 198828502667
Weight	330 g
What's in the box	Poly Studio A2 Audio Bridge; Mounting plate; CAT 6A cable (3.66 m); Microphone extension cable (8 m); Safety guide; Quick start guide; Warranty card

Logistics

UPC number	(AB1) 199642005488; (AC3) 198828502667
What's in the box	Poly Studio A2 Audio Bridge; Mounting plate; CAT 6A cable (3.66 m); Microphone extension cable (8 m); Safety guide; Quick start guide; Warranty card
Cable length	6 m
Package dimensions (W x D x H)	327 x 213 x 89 mm

Pallet dimensions (W x D x H)	120 x 100 x 154.5 cm (ocean); 120 x 100 x 190 cm (air)
Dimensions (W x D x H)	147 x 103 x 24 mm
Country of origin	Taiwan(ABT, AC3); Thailand(ABT, AC3)
Cartons per layer	10
Cartons per pallet	40 (air); 50 (ocean)
Multiple order quantity	5
Layers per pallet	4 (air); 5 (ocean)
Products per pallet	200 (air); 250 (ocean)
Products per pallet layer	50
Material Type for item	FERT
UNSPSC code	45111704
Package weight	1800 g
Pallet weight	382.2 kg
Weight	330 g
Sustainability	
Country of origin	Taiwan(ABT, AC3); Thailand(ABT, AC3)
End of Life CO2e (kg)	0.5
Energy Usage CO2e (kg)	22
Production CO2e (kg)	71
Sustainability specifications	Contains at least 45% recycled plastic content; Paper-based packaging
Sustainability specifications footnote number	[3,4]
Total CO2e (kg)	100
Transportation CO2e (kg)	3

Specifications

[1] HP Poly StudioNet connects multiple devices over Ethernet, using built-in code to enable direct communication with compatible Poly devices via approved switches and the video device's LLN port.

[2] Poly Lens Manages the Audio Bridge through the primary Poly video device.

[3] Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard.

[4] Percent of paper-based packaging made from sustainably sourced, certified, and recycled fibers.

Legal disclaimer