



NC541XA Security Camera

SONY sensor, 360-degree view. Great for the center of a room. Has a microphone and speaker built-in.

9
MEGA
PIXELS

2mm
LENS

SONY IMAGE
SENSOR

Specifications

Camera Type	Fisheye
Image Sensor	1/1.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	12
Maximum Video Resolution	4000 x 3000
Lens	2mm (H.FOV 360°)
Lens Type	Fixed
Maximum Night IR Distance (M)	5
Image clarity	3
Connectors	RJ-45 , Analog Video Out, Audio In, Audio Out, Alarm in or out *4
Video Compression	H.265, H.265
ONVIF (depends on firmware version)	ONVIF (Profile S, Profile G)
Operating Environment	-30 to +55°C/less than ≤ 95% RH
Dimensions	Ø120 X 55mm
Weight (Net)	0.4
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	<7W
Connectors (web)	RJ-45 , Analog Video Out, Audio In, Audio Out, Alarm in or out *4
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	25 (at 9MP)
Day/Night Mode	Auto
Image Enhancement	Fisheye ceiling/desktop/wall/tilt, VR, cylinder, Panorama 180, Panorama 360, 4PTZ, Fisheye+3PTZ, Fisheye+8PTZ, 3 Panorama 360 PTZ, 8 Panorama 360 PTZ, Rotate, Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Edge Recording slot microSD/SDHC Card	Yes
Video Compression	H.265, H.264 (3 streams)
Audio Streaming	Yes (microphone and speaker included)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP, SMTP, P2P (QR code)
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Power Over Ethernet	Yes
Ethernet	Ethernet (10/100 Base-T)
UPNP	Yes
In The Box	Free Software available from FAQ, Printed quick user guide, Installation template, Mounting screws and plugs
Warranty	3 Year Warranty